



SERIE -SERIES

MC4 - MS4

RPM 2900-HZ50

MOTORE SOMMERSO 4"

SUBMERSIBLE MOTOR 4"

MOTEUR IMMERGEE 4"

CARATTERISTICHE TECNICHE

- Massima temperatura liquido 40°C
- Protezione motor IP68
- Isolamento motori : Classe F
- Voltaggio: monofase 230 V - 50 Hz
- Voltaggio : trifase 400V - 50Hz
- Camicia motore in Acciaio Inox AISI304

TECHNICAL DETAILS

- Max liquid temperature 40°C
- Moteur protection IP68
- Insulation motors : Class F
- Voltage: single-phase 230 -50Hz
- Voltage : three phase 400V -50Hz
- Motor casing in Stainless Steel AISI304

CARACTERISTIQUES TECHNIQUES

- Temperature maxi de l'eau 40°C
- Protection moteur IP68
- Isolation moteurs : Class F
- Voltage: uniphase 230V -50Hz
- Voltage: Triphasé 400V-50Hz
- Corps moteur en acier inox AISI304

MOTORI CADOPPI - CADOPPI MOTORS - MOTEURS CADOPPI



MODELLO TYPE ARTICLE	POTENZA POWER		MONOFASE SINGLE-PHASE UNIPHASE V. 230	TRIFASE THREE PHASE TRIPHASE v. 400	CONDENSATORE CAPACITOR CONDENSATEUR µf	MM	PESO WEIGHT MASSE KG
	Hp	Kw					
MC4-0.75M	0,75	0,55	4,7	-	25	371	8,5
MC4-10M	1	0,75	5,8	-	30	396	9,5
MC4-10T	1	0,75	-	2,2	30	365	9
MC4-15M	1,5	1,1	8,3	-	35	416	10,5
MC4-15T	2	1,1	-	3	30	386	10
MC4-20M	2	1,5	12,5	-	45	441	11,6
MC4-20T	2	1,5	-	4,2	-	420	11
MC4-30M	3	2,2	15	-	70	476	13,2
MC4-30T	3	2,2	-	6,0	-	456	12,5
MC4-40T	4	3	-	7,4	-	620	19
MC4-55T	5,5	4	-	9,5	-	660	26
MC4-75T	7,5	5,5	-	13,0	-	745	32

MOTORI SUMOTO - SUMOTO MOTORS - MOTEURS SUMOTO



MODELLO TYPE ARTICLE	POTENZA POWER		MONOFASE SINGLE-PHASE UNIPHASE V. 230	TRIFASE THREE PHASE TRIPHASE v. 400	CONDENSATORE CAPACITOR CONDENSATEUR µf	MM	PESO WEIGHT MASSE KG
	Hp	Kw					
MS4-075M	0,75	0,55	4,7	-	25	325	7,6
MS4-10M	1	0,75	5,8	-	35	350	8,7
MS4-10T	1	0,75	-	2,2	-	325	7,6
MS4-15M	1,5	1,1	8,3	-	40	385	10,3
MS4-15T	1,5	1,1	-	3,0	-	350	8,7
MS4-20M	2	1,5	12,5	-	60	420	12
MS4-20T	2	1,5	-	4,2	-	385	10,4
MS4-30M	3	2,0	15	-	80	470	14,4
MS4-30T	3	2,0	-	6,0	-	420	12
MS4-40T	4	3,0	-	7,4	-	418	13,1
MS4-55T	5,5	4,0	-	9,5	-	468	15,6
MS4-75T	7,5	5,5	-	13,5	-	538	18,9